



FREEZE BLOCK ELITE

**ULS HEATING OIL &
BIODIESEL FUEL
INSTABILITY
PREVENTER ADDITIVE**

FREEZE BLOCK ELITE is a multifunctional middle distillate fuel additive. **FREEZE BLOCK ELITE** is designed to help prevent fuel stability problems in ultra-low sulfur heating oil and biodiesel blends. It also contains a detergent/dispersant, metal deactivator, pour point depression and a corrosion inhibitor.

For personal safety, first aid, storage and handling, see the safety data sheet (SDS) for product specific information.

Typical Properties

Appearance	dark amber liquid
Specific Gravity, 60°F (15.6°C)	0.901
Density, lb./gal, 60°F, (15.6°C)	7.51
Flash Point, PMCC	112°F
Viscosity, cSt @ 40°C.....	5.83
Pour Point, °F	-40
Recommended Treat Rate.....	1:2,000

FREEZE BLOCK ELITE is a diesel fuel additive that provides the following functional and performance benefits:

- Minimizes fuel oxidation
- Provides stabilization for heating oil and biodiesel blends
- Reduces fuel degradation limiting sludge build up on tank bottoms
- Deactivates yellow metals impact on the fuel system
- Inhibits rust formation protecting tank and entire fuel system from corrosion activity
- Reduces the pour point of the fuel limiting kerosene blending
- Keeps fuel from darkening

PO Box #100
Stockertown, PA 18083
(877) 456-FUEL
info@FuelCellPetrol.com

